



# LUMBER WRAP

## ALL-WEATHER RESISTANT LUMBER PROTECTION

From the market leader in protective fabrics, you can be sure with IPG®'s Lumber Wrap that your product will arrive completely protected. IPG coated woven materials are widely used as protective packaging of a variety of industrial products such as dimensional lumber, engineered wood product and metal coils. IPG has been a major, integrated supplier to the North American lumber industry for over 40 years.

### FEATURES & BENEFITS



Exceptional tear resistance



White wrap helps boost brand awareness and visibility



Custom logo can be printed in up to 3 colors



UV & water resistant



Available in various weave strengths, laminations and coatings



800-565-2000 | [ecp.itape.com](http://ecp.itape.com)



## LUMBER WRAP INFORMATION

MATERIALS	COLORS	WIDTHS	GRAB TENSILE ASTM D5034	TONGUE TEAR ASTM D2261	TRAPEZOIDAL TEAR ASTM D4533	MULLEN BURST ASTM D3786	PLIABILITY	OUTDOOR WEATHERING
SUPREME 2.5 PP (90 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 115 lb (510) / Weft 105 lb (466)	Warp 35 lb (155) / Weft 40 lb (177)	Warp 45 lb (199) / Weft 40 lb (177)	180 psi (1240 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure
SUPREME II PP (95 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 115 lb (510) / Weft 105 lb (466)	Warp 35 lb (155) / Weft 40 lb (177)	Warp 45 lb (199) / Weft 40 lb (177)	180 psi (1240 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure
SUPREME I PP (100 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 125 lb (555) / Weft 115 lb (510)	Warp 35 lb (155) / Weft 35 lb (155)	(Warp 45 lb (199) / Weft 40 lb (177)	190 psi (1309 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure
PREMIUM II PP (110 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 145 lb (644) / Weft 130 lb (577)	Warp 40 lb (177) / Weft 40 lb (177)	Warp 60 lb (266) / Weft 55 lb (244)	220 psi (1515 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure
PREMIUM PP (120 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 115 lb (510) / Weft 110 lb (488)	Warp 40 lb (177) / Weft 45 lb (200)	Warp 55 lb (244) / Weft 45 lb (200)	220 psi (1515 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure
PREMIUM PP (126 GSM)	Black/White Tan/White White/White	11" - 144"	Warp 170 lb (755) / Weft 140 lb (620)	Warp 40 lb (177) / Weft 50 lb (222)	Warp 60 lb (266) / Weft 45 lb (199)	240 psi (1653 kPa)	-40° C or -40° F	>80% strength retained after 6 months outdoor exposure

## QUOTING PROCESS QUESTIONS

- 1: *What are you currently using?*
- 2: *Do you use Roll wrap or covers?*
- 3: *Do you want printed or plain?*
- 4: *How do you want it wound? Print in or Print out*
5. *How much do you purchase per order and how often?*

## REQUIRED INFORMATION TO QUOTE

### 1. Roll Wrap

- Weight i.e. 90 GSM
- Color: Black/White, Tan/White or White/White
- Staple Strips - yes or no
- Material Width
- Roll length
- C-folded or flat
- Printed or plain
- Core size: i.e. 3", 4", 6"
- Core type i.e. paper or plastic
- Packaging requirements

### 2. Sewn covers

- Weight i.e. 90 GSM, etc.
- Color: Black/White, Tan/White, or White/White
- Cover size: Length x Height x Width
- Plain or printed (print layout)
- Packaging requirements



Scan for more info or visit [itape.com/products/lumber-wrap/](https://itape.com/products/lumber-wrap/)

