



# AFT200C, AFT450G, & AFT450W

## DOUBLE-COATED ACRYLIC FOAM TAPES

IPG's acrylic foam tapes are double coated with an aggressive pressure-sensitive acrylic adhesive. This acrylic foam tape is engineered to bond to almost any surface. Excellent resistance to solvents and temperature variances. Conforms well to curves, moves and flexes as needed on applications requiring contortion and bending characteristics. Intended for permanent bond of two surfaces.

### FEATURES & BENEFITS

- Excellent resistance to solvents and temperature variances
- High flexibility
- Unique shock absorption and vibration dampening properties
- Eliminates the need for many mechanical fasteners depending upon the application
- Intended for permanent application



888-898-7834 | itape.com



## PRODUCT ATTRIBUTES

Style	Liner	Backing	Adhesive	Adhesion to Steel (oz/in of width)	Thickness w/ Liner (mils)	Thickness w/o Liner (mils)	Color
AFT200C	PE Red	Acrylic Foam	Acrylic	116 (31.78 N/25mm)	24.8 (0.62mm)	20 (0.50mm)	Clear
AFT450G	PE Red	Acrylic Foam	Acrylic	188 (51 N/25mm)	49.8 (1.26mm)	45 (1.14mm)	Grey
AFT450W	PE Red	Acrylic Foam	Acrylic	179 (49 N/25mm)	49.8 (1.26mm)	45 (1.14mm)	White

Available in logs and slit goods.

## PRODUCT APPLICATIONS

- General purpose
- Mounting and bonding with appliances, electronic devices, signage, graphics, side molding, emblems, and weather stripping

## MARKETS

- General Manufacturing
- Automotive
- Transportation



Scan for more info or visit [itape.com/doublecoated](https://itape.com/doublecoated)

