

# PF3

## COLORED SPECIALTY PAPER MASKING TAPE

### DESCRIPTION

A medium crepe paper masking tape coated with a pressure-sensitive, rubber based adhesive. Product is not printable.

### PRODUCT APPLICATION

Designed for light-weight packaging, bag locking, decorative edging, marking and color coding.

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Medium Crepe
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	32 (8.7 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	19 (83 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	7
<b>Total Thickness</b> (mils) PSTC-133	5.2 (0.13mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	10.6 (2.9 N/25mm)
<b>Application Temp. Range</b>	+50°F ~ +90°F (+10°C ~ +32°C)
<b>Operating Temp. Range</b>	+40°F ~ +200°F (+4°C ~ +93°C)
<b>Colors</b>	Red, Light Green, Dark Green, Yellow, Orange, Light Blue and Dark Blue



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/16

