

# PF3

## SPECIALTY PAPER MASKING TAPE

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

A medium crepe paper masking tape coated with a pressure-sensitive, rubber based adhesive. Product is not printable.

### PRODUCT APPLICATION

Designed for light-weight packaging, bag locking, decorative edging, marking and color coding. Can be used for temporary harness wrapping.


### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Medium Crepe
<b>Adhesive</b>	Synthetic Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	32 (8.7 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	19 (83 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	7
<b>Total Thickness</b> (mils) PSTC-133	5.2 (0.13mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	10.6 (2.9 N/25mm)
<b>Application Temp. Range</b>	+50°F ~ +90°F (+10°C ~ +32°C)
<b>Operating Temp. Range</b>	+40°F ~ +150°F (+4°C ~ +66°C)
<b>Colors</b>	White and Black



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/16