

# 599

## MEDIUM GRADE DOUBLE COATED CREPE PAPER TAPE

### DESCRIPTION

A beige crepe paper tape coated on both sides with an aggressive, pressure-sensitive natural rubber adhesive that bonds equally well on both sides to almost any surface. Features an easy release treated white silicone coated kraft liner. Product is not repulpable.

### PRODUCT APPLICATION

Photograph mounting, carpet installation, steel-rule die (make ready), textile manufacturing (twister room), printing industry, and any application that requires the joining of two surfaces.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/25

IPG®

## TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

|                                                 |                      |
|-------------------------------------------------|----------------------|
| <b>Backing</b>                                  | Crepe Paper          |
| <b>Adhesive</b>                                 | Natural Rubber/Resin |
| <b>Adhesion to Steel</b> (oz. /in.)<br>PSTC-101 | 47 (12.8 N/25mm)     |
| <b>Elongation</b> (% at break)<br>PSTC-131      | 8.5                  |
| <b>Thickness w/o Liner</b> (mils)<br>PSTC-133   | 6 (0.15 mm)          |
| <b>Total Thickness</b> (mils)<br>PSTC-133       | 9 (0.22 mm)          |
| <b>Liner Type</b>                               | White SCK            |
| <b>Tape Color</b>                               | Beige                |

